

**IN THE CLAIMS:**

Please amend claims 1-10, 12-21, and 23, cancel claims 24-40 without prejudice or disclaimer, and add new claims 41-54 as follows.

1. (Currently Amended) A method for handing over a connection of a mobile entity from a first network access entity to a second network access entity, wherein a global address of the first network access entity is not known to the mobile entity, the method comprising ~~the step of:~~

    sending a message including information for identifying the first network access entity from the mobile entity to the second network access entity, which enables the second network entity to direct traffic destined to the first network entity.

2. (Currently Amended) The method according to claim 1, further comprising ~~the step of:~~

    identifying, in the second network access entity, whether the message received from the mobile entity is directed to the first network access entity by checking an address indicated in the message, and checking whether the address is globally routable.

3. (Currently Amended) The method according to claim 2, wherein the ~~step of~~ identifying comprises checking the address to determine whether the address is globally routable or not based on a prefix of the address.

4. (Currently Amended) The method according to claim 1, wherein the ~~step of~~ sending comprises sending the message comprising a Fast Binding Update message.

5. (Currently Amended) The method according to claim 1, wherein the ~~step of~~ sending comprises sending the message before de-establishing a connection between the mobile entity and the first network access entity.

6. (Currently Amended) The method according to claim 1, wherein the ~~step of~~ sending comprises sending the message after de-establishing the connection between the mobile entity and the first network access entity.

7. (Currently Amended) The method according to claim 1, further comprising ~~the step of:~~

receiving at the second network access entity a message from the first network access entity including the global address of the first network access entity.

8. (Currently Amended) The method according to claim 1, further comprising **the step of:**

providing in the second network access entity a mapping table in which the information for identifying the first network access entity received from the mobile entity is mapped to a global address of the first network access entity.

9. (Currently Amended) The method according to claim 1, wherein the **step of** sending comprises sending the information comprising at least one parameter as follows:

an old network identity associated with the first network access entity,

an old access point name,

an identity associated with an access point through which the mobile entity was connected to the first network access entity , and

a link layer address of the mobile entity.

10. (Currently Amended) The method according to claim 1, further comprising **the steps of:**

sending a message including all or part of the information for identifying the first network access entity to a proxy; and

determining, using the proxy, an address of the first network access entity.

11. (Original) The method according to claim 10, further comprising ~~the step of:~~  
forwarding, using the proxy, traffic between the second network access entity and  
the first network access entity.

12. (Currently Amended) The method according to claim 1, further comprising  
~~the step of:~~

monitoring, using the mobile entity, attributes of a network of the first network  
access entity in order to obtain the information for identifying the first network access  
entity.

13. (Currently Amended) The method according to claim 10, further comprising  
~~the step of:~~

determining, using the second network access entity, an address of the proxy based  
on the information for identifying the first network access entity received from the  
mobile entity.

14. (Currently Amended) A method for handing over a connection of a mobile entity from a first network access entity to a second network access entity, wherein a global address of the second network access entity is not known to the mobile entity, the method comprising ~~the step of~~:

sending a message including information for identifying the second network access entity from the mobile entity to the first network access entity, which enables the first network access entity to direct traffic to the second network access entity.

15. (Currently Amended) The method according to claim 14, further comprising ~~the steps of~~:

sending, a message including all or part of the information for identifying the second network access entity to a proxy; and

determining, using the proxy, an address of the second network access entity.

16. (Currently Amended) The method according to claim 15, further comprising ~~the step of~~:

forwarding, using the proxy, traffic between the first network access entity and the second network access entity.

17. (Currently Amended) The method according to claim 14, further comprising  
**the step of:**

monitoring, using the mobile entity, attributes of a network of the second network access entity in order to obtain the information for identifying the second network access entity.

18. (Currently Amended) The method according to claim 15, further comprising  
**the step of:**

determining, using the first network access entity, the address of the proxy based on the information for identifying the second network access entity received from the mobile entity.

19. (Currently Amended) The method according to claim 14, further comprising  
**the step of:**

identifying, in the first network access entity, whether the message received from the mobile entity is directed to the second network access entity by checking an address indicated in the message, and checking whether the address is globally routable.

20. (Currently Amended) The method according to claim 19, wherein the ~~step of~~ identifying comprises checking the address to determine whether the address is globally routable or not based on a prefix of the address.

21. (Currently Amended) The method according to claim 14, wherein the ~~step of~~ sending comprises sending the message comprising a handover Initiate message.

22. (Original) The method according to claim 14, wherein  
providing in the first network access entity a mapping table in which the  
information for identifying the second network access entity received from the mobile  
entity is mapped to a global address of the second network access entity.

23. (Currently Amended) The method according to claim 14, wherein the ~~step of~~ sending comprises sending the information for identifying the second network access entity comprising at least one parameter selected from at least one parameter as follows:

a target network identity,

a target access point name, and

an identity associated with an access point through which the mobile entity connects to the second network access entity.

24-40. (Cancelled)

41. (New) A mobile entity of network system comprising a first network access entity and a second network access entity, wherein a global address of the first network access entity is not known to the mobile entity, wherein

the mobile entity is configured to send a message including information for identifying the first network access entity to the second network access entity which enables the second network access entity to direct traffic to the first network access entity.

42. (New) The mobile entity according to claim 41, wherein the message is a Fast Binding Update (F-BU) message.

43. (New) The mobile entity according to claim 41, wherein the information for identifying the first network access entity comprises at least one of the following parameters:

old network identity associated with the first network access entity,

old access point name,



identity associated with the access point through which the mobile entity was connected to the first network access entity, and/or  
a link layer address of the mobile entity.

44. (New) The mobile entity according to claim 41, wherein the mobile entity is configured to monitor attributes of the network of the second network access entity in order to obtain information for identifying the second network access entity.

45. (New) A mobile entity of a network system comprising a first network access entity and a second network access entity, wherein a global address of the second network access entity is not known to the mobile entity, wherein

the mobile entity is configured to send a message including information for identifying the second network access entity to the first network access entity, which enables the first network access entity to direct traffic to the second network access entity.

46. (New) The mobile entity according to claim 45, wherein the mobile entity is configured to monitor attributes of the network of the second network access entity in order to obtain information for identifying the second network access entity.

47. (New) The mobile entity according to claim 45, wherein the message is a handover Initiate (HI) message.

48. (New) The mobile entity according to claim 45, wherein the information for identifying the second network access entity comprises at least one of the following parameters:

- a target network identity,
- target access point name,
- identity associated with the access point through which the mobile entity will be connected to the second network access entity.

49. (New) A computer program embodied on a computer readable medium, the computer readable medium storing computer executable instructions configured to control a processor to perform a method comprising:

- sending a message including information for identifying a first network access entity from a mobile entity to a second network access entity, which enables the second network entity to direct traffic destined to the first network entity, wherein a global address of the first network access entity is not known to the mobile entity.

50. (New) A computer program embodied on a computer readable medium, the computer readable medium storing computer executable instructions configured to control a processor to perform a method comprising:

    sending a message including information for identifying a second network access entity from a mobile entity to a first network access entity, which enables the first network entity to direct traffic destined to the second network entity, wherein a global address of the first network access entity is not known to the mobile entity.

51. (New) A first network access entity configured to:

    receive a message from a mobile entity, the message including information for identifying a second network access entity to the first network access entity, wherein a global address of the second network access entity is not known to the mobile entity, and wherein said message enables the first network entity to direct traffic to the second network access entity.

52. (New) A mobile entity of network system comprising a first network access entity and a second network access entity, wherein a global address of the first network access entity is not known to the mobile entity, wherein

    the mobile entity comprises sending means for sending a message including information for identifying the first network access entity to the second network access

entity which enables the second network access entity to direct traffic to the first network access entity.

53. (New) A mobile entity of a network system comprising a first network access entity and a second network access entity, wherein a global address of the second network access entity is not known to the mobile entity,

wherein the mobile entity comprises sending means for sending a message including information for identifying the second network access entity to the first network access entity, which enables the first network access entity to direct traffic to the second network access entity.

54. (New) A first network access entity, comprising:

receiving means for receiving a message from a mobile entity, the message including information for identifying a second network access entity to the first network access entity, wherein a global address of the second network access entity is not known to the mobile entity, and wherein said message enables the first network entity to direct traffic to the second network access entity.